



Applications
Brochure

CORROSION MAPPING SOLUTIONS

Keep critical assets in safe operating condition

The complete turnkey phased array ultrasonic testing (PAUT) solution comprising instruments, scanners, and probes to cover a wide range of applications.

THE BEYOND CURRENT SOLUTION

It is well known and documented that corrosion and erosion are universal integrity threats across many industry sectors. Inspecting for the reduction in wall thickness of industrial components can help asset managers calculate corrosion rates, plan remedial maintenance, and most importantly, prevent potential loss of containment incidents that have significant cost and environmental impact.

Eddyfi Technologies provides a comprehensive range of highly innovative ultrasonic corrosion inspection solutions. The non-intrusive technique is typically utilized on the external surface of a test component, providing a 2D map representing the condition and visually highlighting variations in material thickness due to material loss, graphically portrayed as an easy to interpret picture. The data sets are fully recordable which carries a wealth of benefits including offline analysis and repeatability. This improves accuracy for repeat surveys and auditable data, suiting compliance within industry regulations. Each of these benefits help control the exclusion of human error, and as a result, increased probability of detection (POD) and accuracy of results.

Eddyfi Technologies offers a complete solution with advanced phased array instruments, a range of automated and manual scanners, and a full range of probes and wedges. Our team of technical experts have invested time in creating ready made kits ensuring we deliver highly optimized turnkey solutions.

The technical expert driven solutions are available in both conventional and phased array ultrasonic testing method types. Due to the larger footprint of PAUT probes, productivity is significantly increased and the data benefits from enhanced resolution, resulting in a high POD and sizing accuracy. Recognition from various inspection bodies and asset integrity engineers has resulted in PAUT becoming the preferred technique and is widely used for the in-service detection and characterization of corrosion in pipes, tanks, vessels, and other critical assets.

Our solutions consist of advanced phased array instruments, semi-automated and manually encoded scanners, and a full range of probes and accessories. The software driving the instruments benefit from many corrosion specific features; these tools simplify and streamline setup through to analysis and reporting, which help demonstrate the inspection campaign results to asset owners. In addition to this, users gain inspection efficiency and an enhanced user experience.

- Simple workflow for setup creation and adaptation
- Dynamic floating gates maximizing detection capabilities and thickness accuracy
- Auto-sizing feature to automatically size and group areas of corrosion
- Time-based synchronization optimizing clean data sets
- 3D C-scan mapping
- Streamlined reporting
- Remote login options – setup/data capture/analysis

Discover a new era of precision with Eddyfi Technologies’ high-quality NDT probes and transducers: [View Probe Catalog](#)




Figure 1: Assisted analysis for corrosion detection and sizing.

APPLICATIONS

- Pressure vessels
- Storage tanks
- Pipelines
- Spheres
- Restricted access areas
- Ship hulls and other marine vessels
- Other critical assets

ADVANCED CORROSION MAPPING TECHNIQUES

Choosing the appropriate corrosion mapping technique is essential for accurate inspection results.

SELECTING THE BEST METHOD FOR YOUR INSPECTION NEEDS

The pulse echo phased array technique electronically generates multiple beam angles, similar to conventional ultrasonic testing (UT), which provides digital imaging for easier detection, positioning, and sizing. There are several options to consider when selecting the corrosion mapping technique, each with its advantages depending on the inspection requirements and conditions:

- **Local Immersion PAUT:** Utilizing the Aqualock waterbox and generally a 7.5MHz 64EL probe, the ultrasound propagates through a column of water. This eliminates the need for a wedge, thus providing the benefits of improved signal consistency, accuracy, and a limited dead zone.
- **Dual Linear Array:** This contact method is often chosen for its near-surface resolution capabilities due to having no interface echo, with minimum remaining wall thickness sizing capabilities of approximately 1.0mm (0.04in). These probes are a great choice for general corrosion, pitting, and even high temperature hydrogen attack (HTHA)/hydrogen induced cracking (HIC)/stress corrosion cracking (SCC). Suitable for total focusing method (TFM)/phase coherence imaging (PCI), the preferred option for these techniques is utilizing the 10MHz version. An additional advantage is that the probe can be removed from the scanner for live scanning of restricted areas.



Figure 2: Local immersion PAUT probe.



Figure 3: Dual linear array probe.

- **Linear Array:** Also a contact method, standard PAUT probes can be utilized with a 0L wedge to take advantage of TFM/PCI techniques.



Figure 4: Linear array probe.

- **Conventional UT:** Our recommended conventional UT option when paired with an automated system is utilizing a single crystal probe with a local immersion water column, housed in a gimbaled holder. Advanced surveys can be deployed without the requirement for phased array qualified personnel, while still taking full advantage of corrosion mapping benefits, including application-specific software features, also available with twin crystal UT.
- **Dry coupled UT:** Specific to the **Scorpion 2** system, this patented twin crystal wheel probe eliminates the need for couplant or a constant water supply, unlike typical ultrasonic probes.




Figure 5: Single crystal probe with a local immersion water column.



Figure 6: Twin crystal wheel probe.

INSPECTION SOLUTIONS

Our instruments offer inspection techniques through semi-automated or motorized scanners, for accurate data acquisition, ensuring 100% coverage, high POD, and precise positioning. Eddyfi Technologies' corrosion scanners provide efficient coverage for diverse geometries, ensuring thorough corrosion mapping.

AUTOMATED SOLUTION

The automated, robust, field-proven **NAV2** robotic scanner has multiple configuration options. The system is capable of high-speed phased array (PAUT and conventional UT) corrosion mapping, elevated-temperature corrosion mapping, and weld inspection utilizing both PAUT and TOFD probes.

- From 75mm (3in) OD to flat
- Ultra low profile
- Battery operated and remote controlled
- Max speed 250mm (9.8in)/sec
- Elevated temperatures up to 150°C (302°F)
- Versatile




Figure 7: NAV2 automated crawler for corrosion and weld inspection.

The **Swift™** and **Scorpion® 2** dry-coupled remote-access and battery-operated ultrasonic crawler brings major efficiency and data improvements to tank shell inspections and other structures such as vessels and offshore installations.

API 650/653 compliant, this powerful system is the perfect solution for in-service inspection of large assets.



Figure 8: Swift and Scorpion 2 remote-access tank shell ultrasonic inspection solution.



Figure 9: Scorpion 2 inspecting tank roof.

SEMI-AUTOMATED SOLUTION

The **NDT Sweeper** is a semi-automated multi-application scanner with a focus on corrosion mapping. This scanner gives a live 2D encoder position using omni-wheels for high speed accurate mapping, also capable of performing weld inspection.

- From 100mm (4in) OD to flat
- 2D mapping – dual encoder
- Omni-wheels
- Versatile
- Integrated braking system
- Lightweight



Figure 10: Semi-automated NDT Sweeper for corrosion and weld inspections.

The **NDT PaintBrush** is an advanced semi-automated corrosion mapping scanner designed for optimal versatility. Its double encoded wheels allow tracking of probe position and orientation, while also allowing accurate mapping even around obstacles.

- Easy setup and onboard controls
- Easy to deploy and able to encode in raster scan over long distances
- Compact, lightweight, and portable
- Live location and probe orientation on screen



Figure 11: NDT PaintBrush coupled with the industry-leading TOPAZ® ultrasonic instrument.

When there is need to cover larger areas, the use of a lightweight fixed frame XY scanner may be the preferred choice. Boasting an array of application deployment options including the aquablock waterbox for localized immersion corrosion mapping, linear array probes with 0L wedge and dual linear array probes.

- 750mm (29.5in) frame bar with ruler
- Dual encoder - scan and index axis
- Suitable for complete mapping of large surfaces
- Lightweight
- Accurate XY position



Figure 12: Compatible with local immersion corrosion mapping for high tolerance to surface roughness and imperfections.

MANUAL ENCODED SOLUTION

The ODI is a manual encoded scanner capable of multiple applications. This C-Clamp device can securely hold wedges measuring up to 55mm (2in) with standard arms or up to 75mm (3in) with the large arms.

- Entry-level solution
- Easy to use
- Versatile
- Lightweight




Figure 13: ODI manual encoded scanner.

ORDERING INFORMATION

Automated Two-Axis Corrosion Mapping

Battery operated and fully remote controlled for inspection of pressure vessels, storage tanks, pipelines, spheres, ship hulls plus other critical assets.

ITEM	DESCRIPTION
Solution kit is compatible with the following instruments: Mantis™, Gekko®, TOPAZ®, Emerald, Panther™	
NAV2-SYSTEM-15M*	Automated, battery operated and remotely controlled crawler system – Includes base crawler, control box, 2 x batteries, umbilical, irrigation, cable management, joystick plus accessories. For diameters 3”+.
AUTO-RASTER-ARM-300MM	Motorized Raster Arm adds two-axis automated scan capabilities to automated crawlers. Can carry many different probes for various types of corrosion scans. Available in 300/600/900/1160mm lengths.
PROBE-SCUT-KIT-15M**	Standard kit for single crystal corrosion inspection. Includes: Single crystal UT probes (5.0MHz-Ø10mm-50FL-SCUT-BNC & 5.0MHz-Ø10mm-75FL-SCUT-BNC), delay line, probe holder compatible with RASTER arm and UT cables - 15m
PROBE-PACM-KIT-15M**	Standard kit for Phased Array UT corrosion inspection. Includes: Phased Array Probe (7.5L64-I4A-64x7-15-IPEX), delay lines, probe holder compatible with RASTER arm - 15m.
MOTORIZED-PUMP	The motorized couplant pump is a powered pumping unit used for supplying couplant fluid to the scanning surface.

NOTE: Enquire for Twin crystal options

*Available in 5m & 30m length.

**Various frequency, cable lengths and connector types available.

Automated One-Axis Corrosion Mapping

Battery operated and fully remote controlled for inspection of pressure vessels, storage tanks, spheres, ship hulls plus other critical assets.

ITEM	DESCRIPTION
DCP-SWIFT-UT	Swift™ UT portable unit. Incl. a premium-quality 26.4cm (10.4in) multi-touch display and high-capacity 100GB SSD. Software for B-Scan, integrated joystick, AC PS, 2x hot swap. Li-ion batt. w/charger, manual & transport case. For Scorpion 2 crawler.
SC2-DCP-CRAWLER	Scorpion 2 fast 4-wheel drive battery operated motorized crawler with 5 MHz dry coupled UT wheel probe. Includes encoder, 50m (165ft) umbilical, 2x swappable Li-ion batteries, external battery charger, maintenance kit, manual & transport case. Requires SWIFT-UT.
SC2-RSCAN-UT-CAL-KIT	Scorpion 2 and Rscan calibration kit. Includes UT reference step wedge 5-10-15-20mm and custom holder to interface with Scorpion2 probe. Also available in Imperial.
SC2-SERVICING-KIT	SC2 Comprehensive Servicing Kit, 1 x Silicon Oil, Cleaning Pads, Cork Washer, Pair of probe tyres, includes required circlips, screws, bearings, gasket & wear runner
EDDYFI-HARNESS-MD	Harness, medium size – Durable nylon with release buckles. Fits waist size from 86 to 122 cm (34” to 48”), chest size from 112 to 137 cm (44” to 54”).
SC2-DCP-SYST-SP-N3	Scorpion 2 & Swift 3 year Service Plan. Includes annual calibrations and comprehensive servicing for 3 years.

NOTE: Alternative One-Axis options available through use of the Nav2 system. Enquire within for more details.

ORDERING INFORMATION

Semi-Automated Corrosion Mapping

NDT Sweeper - Handheld live 2-axis encoding for inspection of pipelines, pressure vessels, storage tanks, spheres, composites plus other critical assets. Contact PAUT method.

ITEM	DESCRIPTION
Solution kit is compatible with the following instruments: Mantis™, Gekko®, TOPAZ®, Emerald, Panther™	
SCAN-SWEEPER-LE*	NDT Sweeper is a 2D manual scanner designed with poly wheels for easy movement in the scan and index direction, scanning on flat or curved surfaces (4"+). The NDT Sweeper features 1 individual probe suspension that can be fixed axially or laterally.
5DL2x32-CL-2x(48X5)-5-IPEX*	2x32-element dual linear array probe - 5MHz - Active aperture of 48mm x 5mm - Pitch A: 1.5mm - Elevation: 5mm - CL casing - 5m cable - IPEX connector.
SCAN-ACC-DLA-SHOE-4IR-65MM	Probe holder for DLA - 5DL2x32-CL-2x(48X5) - 4x Irrigation Ports. This item is a mandatory requirement for the pairing of the Probe to the Sweeper/Paintbrush.
SCAN-SWEEPER-SPARE WHEELS	NDT Sweeper - Kit of Spare Wheels (5x)
SCAN-MANUAL-PUMP-4MM	Manual water pump - 7.9 L - Supplied with irrigation kit for Semi-automated scanners.

*Various frequency, cable lengths and connector types available.

NDT PaintBrush - Handheld live 2-axis encoding for inspection of pipelines, pressure vessels, storage tanks, spheres, composites plus other critical assets. Contact PAUT method.

ITEM	DESCRIPTION
Solution kit is compatible with the following instruments: TOPAZ®	
SCAN-PAINTBRUSH-5M-DE15*	Corrosion Paintbrush scanner with magnetic wheels configuration & encoder cable length 5m. Supports scanning on flat or curved surfaces (4"+). Kit includes tools for scanner maintenance and transport box.
5DL2x32-CL-2x(48X5)-5-IPEX**	2x32-element dual linear array probe - 5MHz - Active aperture of 48mm x 5mm - Pitch A: 1.5mm - Elevation: 5mm - CL casing - 5m cable - IPEX connector.
SCAN-ACC-DLA-SHOE-4IR-65MM	Probe holder for DLA - 5DL2x32-CL-2x(48X5) - 4x Irrigation Ports. This item is a mandatory requirement for the pairing of the Probe to the Sweeper/Paintbrush.
SCAN-MANUAL-PUMP-4MM	Manual water pump - 7.9 L - Supplied with irrigation kit for Semi-automated scanners.

*Available in 3m & 5m lengths.

**Various frequency, cable lengths and connector types available.

Magnetic XY Frame scanner - Handheld 2-axis encoding for inspection of pipelines, pressure vessels, storage tanks, spheres plus other critical assets. Local immersion (Waterbox) & contact testing PAUT methods.

ITEM	DESCRIPTION
Solution kit is compatible with the following instruments: Mantis™, Gekko®, TOPAZ®, Emerald, Panther™	
SCAN-STIX-CORR-LE	Semi-automated corrosion mapping scanner - 4in to flat. Includes 75cm (29.5") frame, heavy duty probe holder (Aqualock cart and waterbox sold separately), 4mm irrigation, 7.5m Lemo encoder cable, index encoder and cable management.
SCAN-AQUA-CART	Aqualock cart is the perfect solution for securely holding the Aqualock waterbox, which carries the Immersion 'I4' probe. Compatible with automated and semi-automated scanners.
7.5L64-I4A-64x7-5-IPEX**	64-element linear array probe - 7.5MHz - Active aperture of 64mm x 7mm - Pitch: 1mm - Elevation: 7mm - I4-A casing - 5m cable - IPEX connector - Select for use with the Aqualock
PROBE-SPARE-FOAM	25 replacement adhesive waterbox foams - 15 white PTFE contact face & 10 clear UHMW contact face for use with Aqualock waterbox.
SCAN-MANUAL-PUMP-4MM	Manual water pump - 7.9 L - Supplied with irrigation kit for semi-automated scanners.

NOTE: For contact DLA corrosion mapping - AUTO-SPARE-ZERO-ADPT is required to hold probe and shoe.

*Available in 15m length.

**Various frequency, cable lengths and connector types available.

ORDERING INFORMATION

Manual Encoded Corrosion Mapping

ODI - Handheld 1-axis encoding for inspection of pipelines, pressure vessels, storage tanks, spheres, composites plus other critical assets. Contact PAUT method.

ITEM	DESCRIPTION
Solution kit is compatible with the following instruments: Mantis™, Gekko®, TOPAZ®, Emerald, Panther™	
SCAN-ODI-1PA-LE	ODI scanner - 1 probe - LEMO 16 Encoder connector - Cable length 2.5 m - Max Clamp Width: 55 mm - Encoder Resolution: 16.0 counts/mm.
5DL2x32-CL-2x(48X5)-2.5-IPEX *	2x32-element dual linear array probe - 5MHz - Active aperture of 48mm x 5mm - Pitch A: 1.5mm - Elevation: 5mm - CL casing - 2.5m cable - IPEX connector.
SCAN-ACC-DLA-SHOE-4IR-65MM	Probe holder for DLA - 5DL2x32-CL-2x(48X5) - 4x Irrigation Ports. This item is a mandatory requirement for the pairing of the Probe to the Sweeper/Paintbrush (Optional for ODI).
SCAN-MANUAL-PUMP-4MM	Manual water pump - 7.9 L - Supplied with irrigation kit for Semi-automated scanners.

*Various frequency, cable lengths and connector types available.

Dual Linear Array Probes

Contact PAUT dual linear array probe options. NOTE: CL type compatible with 65mm (2.56in) probe holder and CS type compatible with 41mm (1.61in) probe holder.

ITEM	DESCRIPTION
5DL2x32-CL-2x(48X5)-2.5-IPEX	2x32-element dual linear array probe - 5MHz - Active aperture of 48mm x 5mm - Pitch A: 1.5mm - Elevation: 5mm - CL casing - 2.5m cable - IPEX connector. Requires ACC-DLA-PRBHOLD-4IR-65mm.
5DL2x32-CS-2x(24X5)-2.5-IPEX	2x32-element dual linear array probe - 5MHz - Active aperture of 24mm x 5mm - Pitch A: 0.75mm - Elevation: 5mm - CS casing - 2.5m cable - IPEX connector. Requires ACC-DLA-PRBHOLD-4IR-41mm.
10DL2x64-DLA-TFM-2x(24X5)-2.5-IPEX	2x64-element dual linear array probe - 10MHz - Active aperture of 24mm x 5mm - Pitch : 0.375mm - Elevation: 5mm - DLA-TFM casing - 2.5m cable - IPEX connector. Requires ACC-DLA-PRBHOLD-4IR-41mm.

*Various frequency, cable lengths and connector types available.

Please note that although they still bear the Zetec logo and branding, the ultrasound instruments and software products are manufactured by Eddyfi Technologies, whereas Zetec branded EC and SG products are manufactured by Zetec Inc. Although affiliated to Eddyfi Technologies, Zetec Inc. remains an independently managed company because of contractual obligations with the US government as a key supplier for classified business. The information in this document is accurate as of its publication. Actual products may differ from those presented herein. © 2024 Eddyfi Canada Inc. Gekko, Mantis, TOPAZ, Capture, and their associated logos are trademarks or registered trademarks of Eddyfi Technologies in the United States and/or other countries. Eddyfi Technologies reserves the right to change product offerings and specifications without notice. Eddyfi Technologies is a Previa Business Unit.